



Hardwear 24 Attached Cushion (HW)

DESCRIPTION: Hardwear 24 is an attached cushion composed of high density, reaction bonded urethane. Hardwear 24 is applied to carpets with existing finished woven polypropylene backings and allows for “off the shelf” delivery with reduced lead time.

FEATURES: Bifocal™ polymer incorporates soybean oil, a 100% renewable resource as a replacement in a portion of the chemistry used in making polyurethane carpet backings. Bifocal™ polymer made with soybean oil supports the agricultural community, while utilizing a commodity that offers a stable supply year after year. BioCel™ polymer becomes an integral component of the high-performance backing system that is applied to carpets provided by carpet manufacturers. The end product is a high-quality carpet backing that utilizes a polymer derived from a stable supply of soybeans, reducing our dependence on petroleum-based products.

TYPICAL END USES: Corporate and General commercial installations.

Hardwear 24 Attached Cushion Specs	
Approximate weight per square yard	28-32 oz.
Approximate thickness (inches)	.120"
Secondary backing non-woven gray fleece	3.5 oz.
Backing Density (approximate)	18.0 lbs./cubic foot
Compression Set	10 lbs.
Compression Resistance	7 lbs.

ADHESIVES: AtlasMasland Premium carpet adhesive and AtlasMasland Seam Sealer must be properly applied to maintain a moisture resistant properties.

SPECIAL INSTRUCTIONS: Available from AtlasMasland Technical Services at 800-633-046