



LIVING QUARTERS | UNITS

Comfy & Floored atlasmasland.com





Comfortable living experiences, by design.


Created for multi-family interiors, Living Quarters is a coordinated duo of soft-surface Comfy and Floored LVT that provides harmony and comfort to connect you to your dwelling space. Presented in soothing, neutral tones, Comfy's *Reconnect* and *Restore* styles feature a supple cut and loop construction that effortlessly blends a pleasant texture with elegant patterning, while Floored features the sophisticated visual texture of natural wood.

Check out our collections at **atlasmasland.com** and discover how we are designing better experiences for interior environments.


COVER IMAGE: Restore SHOWN IN 08 FRESH COFFEE AND Floored SHOWN IN DW003 FRENCH VANILLA



Comfy Color Line SHOWN IN 7136 RECONNECT



31601 THROW PILLOW



31603 FAVORITE PLAVI IST



21605 HOT SHOWED




31607 GAME NIGHT



31602 FUZZY SLIPPERS



31604 LAZY DAY



31606 WARM BLANKE



31608 FRESH COFFEE

Floored Color Line



DW001 COOKIE DOUGH



DW002 ALMOND FUDGE



DW003 FRENCH VANILLA



DW004 BANANA SPLIT



DW005 CHOCOLATE CHIP



DW006 ROCKY ROAD



DW007 BUTTERED PECAN

The Living Quarters color palette features a full range of enhanced neutrals that easily coordinate with any design scheme while bringing tranquility and beauty to every room experience.

From the subtle promise of Warm Blanket to the nostalgic familiarity of Butter Pecan and everything in between, Comfy and Floored are well coordinated to provide easy flooring solutions for your specific multi-family residential environment.





For the most accurate color representation, please request a sample by contacting Customer Service at **1-888-633-4770** or by visiting **atlasmasland.com**.



AtlasMasland is motivated by the aspirations of people and businesses who wish to create unique and positive experiences with every environment they pursue.

A leading manufacturer of technically sophisticated flooring solutions, AtlasMasland draws on a heritage of craftsmanship that spans more than 150 years.

Whether through our statementmaking patterns or customized programs that are tailored to taste, AtlasMasland persistently innovates to inspire our customer's creative freedom in every way.

Comfy

Construction

Reconnect Restore
Style Number 7136 7137

Fiber Content 100% BCF nylon 6,6 Construction Cut / Loop

Pattern Repeat 18"W x 22"L (45.72cm x 55.88cm)

Dye Method Continuous Dyed

Gauge 1/8

Pile Height .375"/.250" (9.52mm/6.35mm)

Primary Backing Polypropylene Secondary Backing Action Bac GLP Certification GLP100079

Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.

.5"W x .75"L (1.27cm x 1.91cm)

Performance

Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program

Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1

Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as

ASTM D-2859

Smoke Density Passes NBS Smoke Chamber Test ASTM E-662

Colorfastness to Light 4.0 or better

Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet

Warranty Limited 10-year Wear Warranty

Floored LVT

Product Specifications

Packaging

Style	8444	Tile Size	5.9" x 48.03" (15cm x 122cm)
Construction	High Performance Luxury Vinyl Tile (SPC)	Pieces per box	15
Edge Detail	Micro-beveled Edge	Square feet per box	29.547 (2.745 m²)
Finish	Ironclad	Coverage/Piece	1.97 Sq. Ft. (0.183 m²)
Embossing	Antique Wood	Coverage/Carton	29.547 Sq. Ft. (2.745 m ²)

 Embossing
 Antique Wood
 Coverage/Carton
 29.547 Sq. Ft. (2.745 m²)

 Wear Layer
 12 mil (0.3mm)
 Coverage/Pallet
 48 Cartons (1418.256 Sq. Ft. / 131.76 m²)

 Layers
 0.126" (3.2mm) Extruded Solid Polymer Core (SPC)
 Coverage/Container
 20 Pallets (28365.29 Sq. Ft. / 2635.2 m²)

0.039" (1.0mm) Pre-Attached IXPE Underlayment
Overall Thickness 0.165" (4.2mm)

Installation Type Click

Warranty 10 year Commercial / 15 year Residential *

Testing	TEST	STANDARD	MINIMUM REQUIREMENT	RESULTS
	Critical Radiant Flux	ASTM E648	≥0.45 Watts/cm2 (Class 1)	Passes

Critical Radiant Flux	ASTM E648	≥0.45 Watts/cm2 (Class 1)	Passes
Smoke Density	ASTM E662	≤450	Passes
Slip Resistance	ASTM D2047	N/A	≥0.85 (Dry)
Static Load	ASTM F970	≤0.005", 250 lbs. load	Passes
Static Load Limit	SIM Test	Test to Limit (±0.005")	Passes
Chemical Resistance	ASTM F925	No more than slight change $\Delta E <$	Passes
Resistance to Heat	ASTM F1514	8 avg. max	Passes
Resistance to Light	ASTM F1515	$\Delta E < 8$ avg. max	Passes
Abrasion Resistance	ASTM D4060	N/A	≥5,600 Cycles
Impact Sound Transmission**	ASTM E492	Impact Insulation Class (IIC) ≥50	IIC 64
Airborne Sound Transmission Loss**	ASTM E90	Sound Transmission Class (STC) ≥50	STC 60

^{*} See warranty documentation for full details of terms and conditions ** Tested over 6" concrete slab with drop-ceiling.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976.

Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©11/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com

P.O. Box 11467 Mobile, AL 36671 716 Bill Myles Drive Saraland, AL 36571

