L'Appelle Collection

Construction

Style NumberStyle #105Fiber ContentAntron® Legacy™ type 6,6 nylon (SCS-EPP-01226, an Environmentally Prefera by SCS)	ble Product certified
	ble Product certified
Construction Interloop Patterned Loop	
Pattern Repeat 37.5"W x 75"L	
Dye Method Piece Dyed	
Gauge 5/64	
Tufted Fiber Weight 28 oz./Sq. Yd.	
Total Weight 65 oz./Sq. Yd.	
Pile Height .131"	
Primary Backing Woven Polypropylene	
Secondary Backing Action Bac™	
GLP Certification GLP4428	
Specifications may vary slightly over the life of a product. For current specification atlasmasland.com.	ns, please visit
Performance	
Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Lab Testing Program	pel Plus Carpet
3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet	
Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859	
Smoke Density Passes NBS Smoke Chamber Test ASTM E-662	
Colorfastness to Light 4.0 or better	
Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	
Warranty Limited 10-year Wear Warranty	

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

