Metafora Collection

Construction

Style Number	Finesse Style #B262
Fiber Content	Antron® Lumena™ solution dyed type 6,6 nylon (SCS-EPP-01226, an Environmentally Preferable Product certified by SCS)
Construction	Interloop Patterned Loop
Pattern Repeat	18.75"W x 18.75"L
Dye Method	Solution Dyed
Gauge	5/64
Tufted Fiber Weight	20 oz./Sq. Yd.
Total Weight	57 oz./Sq. Yd.
Pile Height	.116"
Primary Backing	Woven Polypropylene
Secondary Backing	Permian Bac™
GLP Certification	GLP2306
	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.
Performance	
Performance Environmental	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program
	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet
	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program
Environmental	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II
Environmental Flammability Rating	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Environmental Flammability Rating Smoke Density	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Passes NBS Smoke Chamber Test ASTM E-662
Environmental Flammability Rating Smoke Density Colorfastness to Light	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Passes NBS Smoke Chamber Test ASTM E-662 4.0 or better

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

