Metafora Collection

Construction

Style Number	Whimsical Style #B270
Fiber Content	Antron® Lumena™ solution dyed type 6,6 nylon (SCS-EPP-01226, an Environmentally Preferab Product certified by SCS)
Construction	Interloop Patterned Loop
Pattern Repeat	18.75"W x 18.75"L
Dye Method	Solution Dyed
Gauge	5/64
Tufted Fiber Weight	20 oz./Sq. Yd.
Total Weight	57 oz./Sq. Yd.
Pile Height	.127"
Primary Backing	Woven Polypropylene
Secondary Backing	Permian Bac™
Secondary Dacking	
GLP Certification	GLP2306
	GLP2306 Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.
	Specifications may vary slightly over the life of a product. For current specifications, please visit
GLP Certification	Specifications may vary slightly over the life of a product. For current specifications, please visit
GLP Certification	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet
GLP Certification Performance Environmental	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
GLP Certification	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1
GLP Certification Performance Environmental	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253
GLP Certification Performance Environmental	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II
GLP Certification Performance Environmental Flammability Rating	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
GLP Certification Performance Environmental Flammability Rating Smoke Density	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Passes NBS Smoke Chamber Test ASTM E-662

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

