De La Playa Collection

Construction

Style Number	Tulum Style #B209
Fiber Content	Antron® Legacy [™] type 6,6 nylon (SCS-EPP-01226, an Environmentally Preferable Product certified by SCS)
Construction	Visionweave Patterned Cut & Loop
Pattern Repeat	18.75"W x 20.8"L
Dye Method	Piece Dyed
Gauge	1/8
Tufted Fiber Weight	36 oz./Sq. Yd.
Total Weight	73 oz./Sq. Yd.
Pile Height	.298"
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
GLP Certification	GLP4428
	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.
Performance	
Performance	
Environmental	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program
	Testing Program
Environmental	Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II
Environmental Flammability Rating	Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Environmental Flammability Rating Smoke Density	Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Passes NBS Smoke Chamber Test ASTM E-662
Environmental Flammability Rating Smoke Density Colorfastness to Light	Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Passes NBS Smoke Chamber Test ASTM E-662 4.0 or better

Tufted fiber weight denotes specs prior to tip shearing. Tip shearing removes a small amount of fiber, which will vary slightly by product and production run.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571



