

## Adapt Collection

### Construction

|                     |                                                                                                        |
|---------------------|--------------------------------------------------------------------------------------------------------|
|                     | <b>Pebble Plank Carpet Tile</b>                                                                        |
| Style Number        | Style #TM308                                                                                           |
| Fiber Content       | Antron® Lumena™ type 6,6 nylon (SCS-EPP-01226, an Environmentally Preferable Product certified by SCS) |
| Construction        | Interloop Patterned Loop                                                                               |
| Carpet Tile Size    | 12"W x 36"L                                                                                            |
| Dye Method          | Solution Dyed                                                                                          |
| Gauge               | 1/12                                                                                                   |
| Tufted Fiber Weight | 24 oz./Sq. Yd.                                                                                         |
| Total Weight        | 139 oz./Sq. Yd.                                                                                        |
| Average Pile Height | .219                                                                                                   |
| Total Thickness     | 0.34"                                                                                                  |
| Primary Backing     | Synthetic                                                                                              |
| Secondary Backing   | Perma-tile Vinyl Backing System w/Recycled Content                                                     |
| GLP Certification   | GLP5300                                                                                                |

Specifications may vary slightly over the life of a product. For current specifications, please visit [atlasmasland.com](http://atlasmasland.com).

### Performance

|                        |                                                                                                                                                                                                                                                          |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environmental          | Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program<br><br>3 <sup>rd</sup> party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet                                        |
| Flammability Rating    | Flooring Radiant Panel ASTM E-648 and/or NFPA 253<br>Greater than 0.45 watts/CM <sup>2</sup> Class 1 (EU) BFL S 1<br>Surface Flammability of Carpets and Rugs (16 CFR Chapter II<br>Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 |
| Smoke Density          | Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)                                                                                                                                                                                                  |
| Colorfastness to Light | 4.0 or better                                                                                                                                                                                                                                            |
| Static Rating          | Less than 3.5 kV. Antistat warranted for the life of the carpet                                                                                                                                                                                          |
| Warranty               | Limited Lifetime Commercial Warranty                                                                                                                                                                                                                     |

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or [atlasmasland.com](http://atlasmasland.com)  
P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

