## Milestone

## Construction

	Balance
Style Number	7869
Fiber Content	100% Universal Fibers® Type 6,6 nylon with Permanent Stain Resistance
Construction	Patterned Loop
Pattern Repeat	18"W x 7.75"L (45.72 cm x 19.68 cm)
Dye Method	Solution Dyed
Gauge	1/12
Tufted Fiber Weight	30 oz./Sq. Yd. (1017 g/m²)
Total Weight	65 oz./Sq. Yd. (2204 g/m²)
Pile Height	.375"/.250"/.125" (9.52mm/6.35mm/3.18mm)
Primary Backing	Woven Polypropylene
Secondary Backing	Permian MP
GLP Certification	GLP1678
	Specifications may vary slightly over the life of a product. For current specifications, please visit <b>atlasmasland.com</b> ,
Performance	
Environmental	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program
	3 <sup>rd</sup> party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM <sup>2</sup> Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859

3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpetWarrantyLimited 10-year Wear Warranty	Livionnenta	Testing Program
Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet		3 <sup>rd</sup> party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Flammability Rating	Greater than 0.45 watts/CM <sup>2</sup> Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II
Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662
	Colorfastness to Light	4.0 or better
Warranty Limited 10-year Warranty	Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet
	Warranty	Limited 10-year Wear Warranty

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: **1.888.633.4770 or atlasmasland.com** P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

