Fit III

Construction

Record High

Style Number Style #7897

Fiber Content 100% Universal Fibers® BCF nylon with Permanent Stain Resistance

Construction Patterned Loop

Pattern Repeat 24"W x 20"L (60.96 cm x 50.04 cm)

Dye Method Solution Dyed

Gauge 1/12

Tufted Fiber Weight 18 oz./Sq. Yd. (610 g/m²)

Total Weight 52.2 oz./Sq. Yd. (1770 g/m²)

Pile Height 250"/.125" (6.35mm/3.18mm)

Primary Backing Woven Polypropylene

Secondary Backing Woven Polypropylene with Unitary

GLP Certification GLP1678

Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.

Performance

Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet

Testing Program

3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet

Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253

Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1

Surface Flammability of Carpets and Rugs (16 CFR Chapter II

Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859

Smoke Density Passes NBS Smoke Chamber Test ASTM E-662

Colorfastness to Light 4.0 or better

Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet

Warranty Limited 10-year Wear Warranty

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com

P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571







