Natural Elements

Construction

Fiber Content100% Universal Fibers®, Type 6,6 Nylon with Permanent Stain ResistanceConstructionPatterned LoopCarpet Tile Size12"W x 36"L (30.48cm 91.44cm)Dye MethodSolution DyedGauge1/12Tufted Fiber Weight16 oz./Sq. Yd. (542 g/m²)Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.250"/.125" (6.35mm/3.18mm)Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP 1922*Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.Specifications may vary slightly over the life of a product. For current specifications, please visit
Carpet Tile Size12"W x 36"L (30.48cm 91.44cm)Dye MethodSolution DyedGauge1/12Tufted Fiber Weight16 oz./Sq. Yd. (542 g/m²)Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.250"/.125" (6.35mm/3.18mm)Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
Dye MethodSolution DyedGauge1/12Tufted Fiber Weight16 oz./Sq. Yd. (542 g/m²)Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.250"/.125" (6.35mm/3.18mm)Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
Gauge1/12Tufted Fiber Weight16 oz./Sq. Yd. (542 g/m²)Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.250"/.125" (6.35mm/3.18mm)Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
Tufted Fiber Weight16 oz./Sq. Yd. (542 g/m²)Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.250"/.125" (6.35mm/3.18mm)Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.250"/.125" (6.35mm/3.18mm)Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
Pile Height .250"/.125" (6.35mm/3.18mm) Total Thickness .281" (7.14 mm) Primary Backing Synthetic Secondary Backing EarthWise (non-phthalate, contains recycled content) GLP Certification GLP1922 *Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
Total Thickness .281" (7.14 mm) Primary Backing Synthetic Secondary Backing EarthWise (non-phthalate, contains recycled content) GLP Certification GLP1922 *Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
Primary Backing Synthetic Secondary Backing EarthWise (non-phthalate, contains recycled content) GLP Certification GLP1922 *Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
Secondary Backing EarthWise (non-phthalate, contains recycled content) GLP Certification GLP1922 *Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
GLP Certification GLP1922 *Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
*Also offered using Thrive® aby Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.
your AtlasMasland Contract Manager for pricing and information.
Specifications may vary slightly over the life of a product. For current specifications, please visit
atlasmasland.com.
Performance
Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program
3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
Colorfastness to Light 4.0 or better
Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet
Warranty Limited Lifetime Commercial Warranty

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571



