Fit

Construction	
Construction	

	Game Changer Tile
Style Number	Style # T7896
Fiber Content	100% Universal Fibers®, BCF Nylon with Permanent Stain Resistance
Construction	Patterned Loop
Carpet Tile Size	24"W x 24"L (60.96cm x 60.96cm)
Dye Method	Solution Dyed
Gauge	1/12
Tufted Fiber Weight	14 oz./Sq. Yd. (474 g/m²)
Total Weight	106.8 oz./Sq. Yd. (3621 g/m²)
Pile Height	.250"/.125" (6.35mm/3.18mm)
Total Thickness	.312" (7.92 mm)
Primary Backing	Synthetic
Secondary Backing	EarthWise (non-phthalate, contains recycled content)
GLP Certification	GLP1922
	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com .
Performance	
Environmental	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpe Testing Program
	3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
Colorfastness to Light	4.0 or better
Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

