

Fit

Construction

	Found Money
Style Number	Style # T7947
Fiber Content	100% Universal Fibers®, BCF Nylon with Permanent Stain Resistance
Construction	Patterned Loop
Carpet Tile Size	24"W x 24"L (60.96cm x 60.96cm)
Dye Method	Solution Dyed
Gauge	1/12
Tufted Fiber Weight	14 oz./Sq. Yd. (474 g/m ²)
Total Weight	107.58 oz./Sq. Yd. (3648 g/m ²)
Pile Height	.250"/.125" (6.35mm/3.18mm)
Total Thickness	.281" (7.14 mm)
Primary Backing	Synthetic
Secondary Backing	EarthWise (non-phthalate, contains recycled content)
GLP Certification	GLP1922

Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.

Performance

Environmental	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
Colorfastness to Light	4.0 or better
Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet
Warranty	Limited Lifetime Commercial Warranty

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: **1.888.633.4770** or atlasmasland.com
P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

