Inizio / Moda Collection I & II

Construction

by SCS) Construction Textured Loop Pattern Repeat None Dye Method Piece Dyed Gauge 1/10 Tufted Fiber Weight 32 oz./Sq. Yd. Total Weight 69 oz./Sq. Yd. Pile Height .155" Primary Backing Woven Polypropylene Secondary Backing Action Bac™ GLP Certification GLP4428 Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Performance Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/OM Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Surface Flammability OCPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet Warranty Limited 10-year Warranty <th>Style Number Fiber Content</th> <th>Inizio Style #641 Antron® Legacy™ type 6.6 nylon (SCS-EPP-01226, an Environmentally Preferable Product certified</th>	Style Number Fiber Content	Inizio Style #641 Antron® Legacy™ type 6.6 nylon (SCS-EPP-01226, an Environmentally Preferable Product certified
Pattern RepeatNoneDye MethodPiece DyedGauge1/10Tufted Fiber Weight32 oz./Sq. Yd.Total Weight69 oz./Sq. Yd.Pile Height.155"Primary BackingWoven PolypropyleneSecondary BackingAction Bac™GLP CertificationGLP4428Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.Performance		by SCS)
Dye Method GaugePiece Dyed Gauge1/10Tufted Fiber Weight32 oz./Sq. Yd.Total Weight69 oz./Sq. Yd.Pile Height.155"Primary BackingWoven PolypropyleneSecondary BackingAction Bac™GLP CertificationGLP4428Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing ProgramSid* party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CMP Class 1 (EU) CFL S 1 Surface Flammability Of Carpets and Rugs (IR CFR Chapter II 	Construction	Textured Loop
Gauge1/10Tufted Fiber Weight32 oz./Sq. Yd.Total Weight69 oz./Sq. Yd.Pile Height.155"Primary BackingWoven PolypropyleneSecondary BackingAction Bac™GLP CertificationGLP4428Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing ProgramFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CMP CIPLs 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Pattern Repeat	None
Tufted Fiber Weight32 oz/Sq. Yd.Total Weight69 oz/Sq. Yd.Pile Height.155"Primary BackingWoven PolypropyleneSecondary BackingAction Bac TMGLP CertificationGLP4428Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CMP Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Dye Method	Piece Dyed
Total Weight69 oz./Sq. Yd.Pile Height.155"Primary BackingWoven PolypropyleneSecondary BackingAction Bac TMGLP CertificationGLP4428Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CMP Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Gauge	1/10
Pile Height.155"Primary BackingWoven PolypropyleneSecondary BackingAction Bac™GLP CertificationGLP4428Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Tufted Fiber Weight	32 oz./Sq. Yd.
Primary BackingWoven PolypropyleneSecondary BackingAction Bac™GLP CertificationGLP4428Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Total Weight	69 oz./Sq. Yd.
Secondary Backing GLP Certification Action Bac TM GLP4428 Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Performance Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Pile Height	.155"
GLP CertificationGLP4428Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Primary Backing	Woven Polypropylene
Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Performance Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Secondary Backing	Action Bac™
Performance Image: Static Rating Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	GLP Certification	GLP4428
EnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet		
Testing Program3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Performance	
Flammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Environmental	
Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet		3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Flammability Rating	Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II
Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662
	Colorfastness to Light	4.0 or better
Warranty Limited 10-year Wear Warranty	Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet
	Warranty	Limited 10-year Wear Warranty

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

