Shift Your Attitude

Construction

Fiber Content100% Universal Fibers®, Type 6,6 nylon with Permanent Stain ResistanceConstructionPatterned LoopCarpet Tile Size24'W x 24'L (60.96cm x 60.96cm)Dye MethodSolution DyedGauge1/12Tufted Fiber Weight16 oz./5g, Yd. (543 g/m²)Total Weight102.28 oz./Sq, Yd. (3468 g/m²)Pile Height.250'/.187/.125'' (6.35mm/4.76 mm/3.18mm)Total Thickness.281'' (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922"Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information. Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.Performance	Style Number	Tread Style # T7976
ConstructionPatterned LoopCarpet Tile Size24'W x 24'L (60.96cm x 60.96cm)Dye MethodSolution DyedGauge11/2Tufted Fiber Weight16 oz./Sq. Yd. (543 g/m²)Total Weight102.28 oz./Sq. Yd. (3488 g/m²)Pile Height.250''.187/.125'' (6.35mm/4.76 mm/3.18mm)Total Thickness.281" (r.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 	Fiber Content	100% Universal Fibers®, Type 6.6 nylon with Permanent Stain Resistance
Dye MethodSolution DyedGauge1/12Tufted Fiber Weight16 oz/Sq. Yd. (543 g/m²)Total Weight102.28 oz/Sq. Yd. (3468 g/m²)Pile Height.2507/187/.125" (6.35mm/4.76 mm/3.18mm)Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM* Class 1 (EU) BFL S 1 Surface Flammability Of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Construction	
Gauge1/12Tufted Fiber Weight16 oz./Sq. Yd. (543 g/m²)Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.2507/.187/.125" (6.35mm/4.76 mm/3.18mm)Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6.6. Contact your AtlasMasland Contract Manager for pricing and information. Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.Performance	Carpet Tile Size	24"W x 24"L (60.96cm x 60.96cm)
Tufted Fiber Weight16 oz./Sq. Yd. (543 g/m²)Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.2507.187/.125° (6.35mm/4.76 mm/3.18mm)Total Thickness.281° (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing ProgramSid party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Dye Method	Solution Dyed
Total Weight102.28 oz./Sq. Yd. (3468 g/m²)Pile Height.2507/.187/.125' (6.35mm/4.76 mm/3.18mm)Total Thickness.281' (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing ProgramSid party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CMP Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Gauge	1/12
Pile Height .250"/.187/.125" (6.35mm/4.76 mm/3.18mm) Total Thickness .281" (7.14 mm) Primary Backing Synthetic Secondary Backing EarthWise (non-phthalate, contains recycled content) GLP Certification GLP1922 * Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information. Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Performance Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CMP Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode) Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Tufted Fiber Weight	16 oz./Sq. Yd. (543 g/m²)
Total Thickness.281" (7.14 mm)Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information. Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Total Weight	102.28 oz./Sq. Yd. (3468 g/m²)
Primary BackingSyntheticSecondary BackingEarthWise (non-phthalate, contains recycled content)GLP CertificationGLP1922*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information.Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.PerformanceEnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CMP Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Pile Height	.250"/.187/.125" (6.35mm/4.76 mm/3.18mm)
Secondary Backing EarthWise (non-phthalate, contains recycled content) GLP Certification GLP1922 *Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information. Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Performance Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode) Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Total Thickness	.281" (7.14 mm)
GLP Certification GLP1922 *Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information. Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Performance Invironmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CMP Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode) Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Primary Backing	Synthetic
*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your AtlasMasland Contract Manager for pricing and information. Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Performance Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode) Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Secondary Backing	EarthWise (non-phthalate, contains recycled content)
AtlasMasland Contract Manager for pricing and information. Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com. Performance Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode) Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	GLP Certification	GLP1922
Performance Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program 3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859 Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode) Colorfastness to Light 4.0 or better Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet		
EnvironmentalMeets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet		
Testing Program3rd party certified to the NSF / ANSI 140 Sustainability Assessment for CarpetFlammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Performance	
Flammability RatingFlooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Environmental	
Greater than 0.45 watts/CM² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859Smoke DensityPasses NBS Smoke Chamber Test ASTM E-662 (flaming mode)Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet		3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
Colorfastness to Light4.0 or betterStatic RatingLess than 3.5 kV. Antistat warranted for the life of the carpet	Flammability Rating	Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II
Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet	Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
	Colorfastness to Light	4.0 or better
Warranty Limited Lifetime Commercial Warranty	Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet
	Warranty	Limited Lifetime Commercial Warranty

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571



