

## Abstract Specifications

Style	8515
Construction	High Performance Luxury Vinyl Tile
Wear Layer	20 mil (0.5 mm)
Finish	Ironclad Anti-Scratch Ceramic PU Finish (Anti-Bacterial)
Overall Thickness	0.197" (5 mm)
Reference Specification	Class III Printed Film Vinyl Tile, Type B (embossed)

### Installation

Installation Type	Glue Down
Adhesive	AtlasMasland Premium Spray Adhesive or Modular Tile/LVT Adhesive

### Packaging

Tile Size	18" x 36" (45.72cm x 91.44cm)	Coverage/Piece	1.97 Sq. Ft. (0.183 m <sup>2</sup> )
Pieces per box	6	Coverage/Carton	29.547 Sq. Ft. (2.745 m <sup>2</sup> )
Square feet per box	26.9 (2.50 m <sup>2</sup> )	Coverage/Pallet	48 Cartons (1418.256 Sq. Ft. / 131.76 m <sup>2</sup> )
Weight per box	41.89lbs (19kg)		

### Testing

Test	Standard	Minimum Requirement	Results
Critical Radiant Flux	ASTM E648	≥0.45 Watts/cm <sup>2</sup> (Class 1)	Passes
Smoke Density	ASTM E662	≤450	Passes
Slip Resistance	ASTM D2047	ADA Compliant	≥0.6 (Dry)
Dimensional Stability	ASTM F2199	0.02" lin. ft. max	Passes
Flexibility	ASTM F137	≤1.0" (no cracks or breaks)	Passes
Residual Indentation	ASTM F1914	Avg. < 8%	Passes
Static Load	ASTM F970	250 psi min	Passes
Chemical Resistance	ASTM F925	No more than slight change	Passes
Resistance to Heat	ASTM F1514	ΔE < 8 avg. max	Passes
Resistance to Light	ASTM F1515	ΔE < 8 avg. max	Passes
Thickness Tolerance	ASTM F386	±0.005"	Passes
Indoor Air Quality	CHPS 01350 LEED EQ 4.3	Low VOC	FloorScore Certified

### Warranty

10 year – Limited Commercial Wear Warranty      15 year – Light Commercial Wear Warranty

See warranty documentation for full details of terms and conditions.



Order Samples at 1-888-633-4770 or [atlasmasland.com](http://atlasmasland.com) | AtlasMasland | 716 Bill Myles Drive | Saraland, AL 36571

