



## **Quiet Down WPC 20 Specifications**

8525 Quiet Down WPC 20 (Georgia Ash) Style Construction High Performance Luxury Vinyl Tile 0.197" (5.0 mm) Rigid Vinyl Core - Hardicore

Layers

0.079" (2.0 mm) LVT Top

0.059" (1.5 mm) Integral Sound-Mitigating Underlayment (Hush Technology) with Inhibi-Max

Wear Layer 20 mil (0.5 mm) Edge Detail Micro-beveled Edge

Urethane with Ceramic Bead and Inhibi-Max Finish

**Embossing** Natural Timber Overall Thickness 0.335" (8.5 mm)

Installation Type Click

## **Packaging**

Tile Size 7.48" x 47.64" (19cm x 121cm) Coverage/Piece 2.475 Sq. Ft. (0.23 m2) Pieces per box Coverage/Carton 19.8 Sq. Ft. (1.84 m2)

Square feet per box 19.8 (1.84 m2) Coverage/Pallet 48 Cartons (950.4 Sq. Ft. / 88.32 m2)

> Coverage/Container 20 Pallets (19,008 Sq. Ft. / 1,766.4 m2)

## **Testing**

Test	Standard	Minimum Requirement	Results
Critical Radiant Flux	ASTM E648	≥0.45 Watts/cm2 (Class 1)	Passes
Smoke Density	ASTM E662	≤450	Passes
Slip Resistance	ASTM D2047	N/A	≥0.6 (Dry)
Antifungal Activity	ASTM G21	N/A	Top: 0-1; Bottom: 0*
Wear Layer Thickness	ASTM F410	≥20 mil	Passes
Heavy Metals	ASTM F963	Refer to Standard	Passes
Static Load	ASTM F970	±0.005", 250 lbs. load	Passes
Static Load Limit			≥500 lbs.
Chemical Resistance	ASTM F925	No more than slight change	Passes
Resistance to Heat	ASTM F1514	ΔE < 8 avg. max	Passes
Resistance to Light	ASTM F1515	ΔE < 8 avg. max	Passes
Abrasion Resistance	ASTM D4060	N/A	≥25,000 Cycles
Impact Sound Transmission**	ASTM E492	Impact Insulation Class (IIC) ≥50	IIC 65
Airborne Sound Transmission			
Loss**	ASTM E90	Sound Transmission Class (STC) ≥50	STC 59
Indoor Air Quality	CHPS 01350	Low VOC	FloorScore Certified
	LEED EQ 4.3		
Warranty			

15 Year - Limited Commercial Wear Warranty

See warranty documentation for full details of terms and conditions.

\*ASTM G21: Top Surface (LVT): 0-1 (No Growth to < 10% Growth); Bottom Surface (Underlayment): 0 (No Growth) \*\*Tested over 6" concrete slab with drop-ceiling.

