

Calibré Woods Specifications

Style	8523 Calibré Woods
Construction	High Performance Luxury Vinyl Tile
Wear Layer	20 mil (0.5 mm)
Finish	Ironclad Anti-Scratch Ceramic PU Finish (Anti-Bacterial)
Overall Thickness	0.197" (5 mm)
Reference Specification	Class III printed film vinyl tile, type b (embossed)

Installation

Installation Type	Glue Down
Adhesive	AtlasMasland Premium Spray Adhesive or AtlasMasland Modular Tile/LVT Adhesive

Packaging

Tile Size	9.25" x 59.25" (23.495 cm x 150.495 cm)
Pieces per box	6
Square feet per box	22.8(2.12m ²)
Weight per box	35.54 lbs.(16.12kg)

Testing

Test	Standard	Minimum Requirement	Results
Dimensional Stability	ASTM F2199	0.02" lin. ft. max.	Passes
Flexibility	ASTM F137	≤1.0"	Passes
Radiant Panel	ASTM E648	>.45 watts/cm ² (NFPA Class 1)	Passes
Residual Indentation	ASTM 1914	Avg. <8%	Passes
Resistance to Heat	ASTM F1514	ΔE <8% avg. max	Passes
Resistance to Light	ASTM F1515	ΔE <8% avg. max	Passes
Resistance to Chemical	ASTM F925	No more than slight change	Passes
Size Tolerance	ASTM F2421	±0.016"/lin. ft.	Passes
Slip Resistance	ASTM D2047	ADA Compliant	Passes
Smoke Density	ASTM E662	≤450	Passes
Static Load	ASTM F970	250 psi min	Passes
Thickness Tolerance	ASTM F368	±0.005"	Passes
Indoor Air Quality		Low VOC	Floor Score Certified

Warranty

15 Year - Limited Commercial Wear Warranty
See warranty documentation for full details of terms and conditions.



*ASTM G21: Top Surface (LVT): 0-1 (No Growth to < 10% Growth); Bottom Surface (Underlayment): 0 (No Growth)
**Tested over 6" concrete slab with drop-ceiling.

Order Samples at 1-888-633-4770 or atlasmasland.com | AtlasMasland | 716 Bill Myles Drive | Saraland, AL 36571