

## Calibré Fast2Floor (Quick Ship) Specifications

Style	8410 Calibré Fast2Floor (Quick Ship)
Construction	High Performance Luxury Vinyl Tile
Wear Layer	20 mil (0.5 mm)
Finish	Ironclad Anti-Scratch Ceramic PU Finish (Anti-Bacterial)
Overall Thickness	0.118" (3 mm)

### Installation

Installation Type	Glue Down
Adhesive	AtlasMasland Premium Spray Adhesive or AtlasMasland Modular Tile/LVT Adhesive

### Packaging

Tile Size	6" x 48" (15.24 cm x 121.92 cm)
Pieces per box	18
Square feet per box	36.0 (3.34m <sup>2</sup> )
Weight per box	37.17 lbs.(16.86 kg)

### Testing

Test	Standard	Minimum Requirement	Results
Dimensional Stability	ASTM F2199	0.02" lin. ft. max.	Passes
Flexibility	ASTM F137	≤1.0" (No cracks or breaks)	Passes
Radiant Panel	ASTM E648	>.45 watts/cm <sup>2</sup> (NFPA Class 1)	Passes
Residual Indentation	ASTM 1914	Avg. <8%	Passes
Resistance to Heat	ASTM F1514	ΔE <8% avg. max	Passes
Resistance to Light	ASTM F1515	ΔE <8% avg. max	Passes
Resistance to Chemical	ASTM F925	No more than slight change	Passes
Smoke Density	ASTM E662	≤450	Passes
Static Load Limit	ASTM F970	250 psi min	Passes
Indoor Air Quality		Low VOC	Floor Score Certified

### Warranty

10 Year – Limited Commercial Wear Warranty      15 Year - Light Commercial Wear Warranty

See warranty documentation for full details of terms and conditions.



Order Samples at 1-888-633-4770 or atlasmasland.com | AtlasMasland | 716 Bill Myles Drive | Saraland, AL 36571