Hideaway

Construction

Relax

	Relax
Style Number	7997
Fiber Content	100% Universal Fibers® Type 6 nylon
Construction	Patterned Loop
Pattern Repeat	Random
Dye Method	Solution Dyed
Gauge	1/12
Tufted Fiber Weight	12 oz./Sq. Yd. (407 g/m²)
Total Weight	48 oz./Sq. Yd. (1628 g/m²)
Pile Height	.250"/.125" (6.35mm/3.18mm)
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene with Unitary
GLP Certification	GLP1678
	Product manufactured utilizing pre-consumer recycled content. Please see environmental specifications for additional information.
	Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com .
Performance	
Environmental	Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program
	3 rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	
	Passes NBS Smoke Chamber Test ASTM E-662
Colorfastness to Light	Passes NBS Smoke Chamber Test ASTM E-662 4.0 or better
Colorfastness to Light	4.0 or better

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©7/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571

