Dwellings

Construction

Gables

Style Number 7946

Fiber Content 100% PureColor™ Solution Dyed BCF Polyester

Construction Cut and Loop

Pattern Repeat 1.5" W x 1.375"L (3.81 cm x 3.49 cm)

Dye Method Solution Dyed

Gauge 1/10

Tufted Fiber Weight 28 oz./Sq.Yd. (949 g/m2)

Total Weight 59.3 oz./Sq.Yd. (2011 g/m2)

Pile Height .406"/.344" (10.31 mm / 8.74 mm)

Primary Backing Woven Polypropylene
Secondary Backing Woven Polypropylene

GLP Certification GLP2385

Specifications may vary slightly over the life of a product. For current specifications, please visit atlasmasland.com.

Performance

Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet

Testing Program

3rd party certified to the NSF / ANSI 140 Sustainability Assessment for Carpet

Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253

Greater than 0.45 watts/CM² Class 1 (EU) CFL S 1

Surface Flammability of Carpets and Rugs (16 CFR Chapter II

Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859

Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)

Colorfastness to Light 4.0 or better

Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet

Warranty 10-year wear warranty



Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. AtlasMasland matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ©2/2020 AtlasMaslandTM.





