Living Quarters - Comfy

Construction

Restore

Style Number 7137

Fiber Content 100% BCF nylon 6,6

Construction Cut / Loop

Pattern Repeat .5"W x .75"L (1.27cm x 1.91cm)

Dye Method Continuous Dyed

Gauge 1/8

Tufted Fiber Weight 25 oz./Sq. Yd. (848 g/m²)

Total Weight 61 oz./Sq. Yd. (2068 g/m²)

Pile Height .375"/.250" (9.52mm/6.35mm)

Primary Backing Polypropylene
Secondary Backing Action Bac
GLP Certification GLP100079

Specifications may vary slightly over the life of a product. For current specifications, please visit

atlasmasland.com.

Performance

Environmental Meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet

Testing Program

Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253

Greater than 0.45 watts/CM2 Class 1 (EU) CFL S 1

Surface Flammability of Carpets and Rugs (16 CFR Chapter II

Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859

Smoke Density Passes NBS Smoke Chamber Test ASTM E-662

Colorfastness to Light 4.0 or better

Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet

Warranty Limited 10-year Wear Warranty

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All AtlasMasland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of an AtlasMasland design constitutes copyright infringement in violation of federal law. ⊚10/2020 AtlasMasland™.

Order samples: 1.888.633.4770 or atlasmasland.com

P.O. Box 11467 Mobile, AL 36671 | 716 Bill Myles Drive Saraland, AL 36571



