Contemporary Woods

Construction

Airbrushed

Style Number	8528
Construction	High Performance Luxury Vinyl Tile
Finish	Ironclad Plus
Wear Layer	20 mil (0.5mm)
Edge Detail	Micro-beveled Edge
Overall Thickness	0.177″ (4.5mm)
Embossing	Barnside
Installation Type	Glue Down or Magnetic
Adhesive	AtlasMasland Premium Spray Adhesive or Modular Tile/LVT Adhesive
Warranty	15 year – Limited Commercial Wear* / Lifetime – Limited Residential Wear*

Packaging

Tile Size	7″ x 48″ (17.78cm x 121.92cm)
Pieces per box	10
Square feet per box	23.33 (2.17 m²)
Weight per box	39.9 lbs. (18.10kg)
Coverage/Piece	2.33 Sq. Ft. (.216 m²)
Coverage/Carton	23.33 Sq. Ft. (2.17 m²)
Coverage/Pallet	50 Cartons (1166.5 Sq. Ft. / 108 m²)
Coverage/Container	20 Pallets (23330 Sq. Ft. / 2167 m²)

Testing

TEST	STANDARD	MINIMUM REQUIREMENT	RESULTS
Dimensional Stability	ASTM F2199	0.02″ lin. ft. max	Passes
Flexibility	ASTM F137	≤1.0″ (no cracks or breaks)	Passes
Radiant Panel	ASTM E648	≥.45 watts/cm² (NFPA Class 1)	Passes
Residual Indentation	ASTM F1914	Avg.<8%	Passes
Resistance to Heat	ASTM F1514	$\Delta E < 8$ avg.max	Passes
Resistance to Light	ASTM F1515	$\Delta E < 8$ avg.max	Passes
Chemical Resistance	ASTM F925	No more than slight change	Passes
Size Tolerance	ASTM F2421	±0.016″/lin. ft.	Passes
Slip Resistance	ASTM D2047	ADA Compliant	Passes
Smoke Density	ASTM E662	≤450	Passes
Static Load	ASTM F970	250 psi min	Passes
Thickness Tolerance	ASTM F386	±0.005″	Passes
Indoor Air Quality		Low VOC	FloorScore Certified

* See warranty documentation for full details of terms and conditions.

For reclamation of this book, please contact your AtlasMasland contract manager.

Order samples: **1.888.633.4770** or **atlasmasland.com**
P.O. Box 11467   Mobile, AL 36671   716 Bill Myles Drive Saraland, AL 36571