

## **TEST REPORT**

DATE: 03-29-2017	Page 1 of 1	<b>TEST NUMBER</b> : 0235611
CLIENT	Masland Contract	
TEST METHOD CONDUCTED	ASTM F2199 Test Method for Determining Dimensional Stability of Resilient Floor Tile after Exposure to Heat	

DESCRIPTION OF TEST SAMPLE		
IDENTIFICATION	Calibre' Quiet Down LVT 12 mil	
CONSTRUCTION	Vinyl Plank	

## **GENERAL PRINCIPLE**

This test method is intended for use in determining the linear change of resilient flooring after being exposed to heat. The dimensional change over 12 inches is reported as the dimensional stability.

## **TEST RESULTS**

REPLICATE	IDENTIFICATION	RESULT
#1	Length	-0.007 Inch per 12 inches (-0.06%)
	Width	-0.008 Inch per 12 inches (-0.07%)
#2	Length	-0.006 Inch per 12 inches (-0.05%)
	Width	-0.006 Inch per 12 inches (-0.05%)
#3	Length	-0.007 Inch per 12 inches (-0.06%)
	Width	-0.008 Inch per 12 inches (-0.07%)

Lang atluny APPROVED BY:

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical of similar products. This report, or the name of Professional Testing Laboratory Inc. shall not be used under any circumstance in advertising to the general public.